

Ishida AC-4000/B/E Price Computing Scale with Printer



Available
January 2004!



Approvals



PART #	MODEL	CAPACITY
80808	AC-4000	15 lb x 0.005 lb 30 lb x 0.01 lb
79477	AC-4000B	15 lb x 0.005 lb 30 lb x 0.01 lb
80318	AC-4000E	15 lb x 0.005 lb 30 lb x 0.01 lb

Networking capabilities along with user-friendly operation make the new AC-4000 an ideal supermarket scale for bakeries, delis, seafood, meat and produce applications. The AC-4000 communicates via Ethernet, RF wireless transmission, and supports Dynamic Host Configuration Protocol (DHCP). Choose from multiple label formats and use the powerful batch printing feature for increased productivity.

AC-4000

- Bright alphanumeric display for customized messages
- Smart cassette design allows for quick label changes

AC-4000B

- Bright alphanumeric display for customized messages
- Internal printer offers label and report printing options

AC-4000E

- Economic version for quick price computing
- Bright numeric display offers weight and price information
- Internal printer offers label and report printing options



AC-4000E



AC-4000

Applications

- Meat, seafood, deli, produce, and bakery departments

Standard Features

- Static or dynamic (DHCP) TCP/IP Ethernet communication
- Flash ROM for remote update of application software
- Fast printing speed results in greater customer throughput
- Multiple label formats for multi-department support
- Powerful batch printing feature frees operator's time
- 184 function keys assist with intuitive operation (PLU, tare, price, multiple, special price, price discount, percent discount, void, extra message, proportional tare and more)
- Bright dot matrix display for alphanumeric messaging
- 2 MB standard memory
- Proportional tare

Options/Accessories

- 80309**.....Internal 802.11b wireless communications (powered by Agere's™ Ruby™ RF chipset compatible with 802.11b/Wifi™ devices) PCMCIA card included
- 46916**.....Produce platter
- 46917**.....Fish platter
- 71199**.....Polyethylene scale shelf, white (18.75"W x 17"D x 1"H)
- 65231***.....ScaleLink Pro Software

LABEL STOCK

- 47732**.....2.36" x 1.73" (60mm x 44mm)
- 47733**.....2.52" x 1.85" (64mm x 47mm)
- 47735**.....Extended text, 2.52" x 2.32" (64mm x 59mm)
- 47736**.....Pre-printed safe handling instructions, 2.52" x 2.32" (64mm x 59mm)
- 47743****.....Extended text, 2.52" x 3.34" (64mm x 85mm)
- 47745**.....Pre-printed safe handling instructions on top of label, 2.52" x 3.34" (64mm x 85mm)
- 47762**.....Non-barcode, 2.52" x 1.46" (64mm x 37mm)
- 47749**.....Bakery label 2.60" x 5.71" (66mm x 145mm)
- 47751**.....Bakery label 2.52" x 4.33" (64mm x 110mm)
- 47747**.....Coupon label 2.60" x 3.31" (66mm x 84mm)
- 47761**.....Continuous 2.52" (64mm)

SERVICE TOOLS

- 77369*****....CD-ROM contains (i-View, i-Label, firmware update tool, manuals)
- 77368**.....BIOS Eprom kit

MANUALS

- 80385*****....Service manual
- 80811*****....Additional programmers manual
- 80812*****....Additional operation manual

* License file required for operation. Must supply store name and address at time of order. One license required per location.

** Safe handling instructions can also be printed by scale.

*** Manuals and software programs can be downloaded for FREE from the distributor section of the Ishida website at www.ishidaretail.com

CAPACITY/MINIMUM GRADUATION:

15 x 0.005/30 x 0.01lb (dual range)
 30 x 0.01 (single-range), selectable

DISPLAY ITEMS:

Tare: 4 digits
 Unit price: 5 digits
 Weight: 5 digits
 Total Price: 6 digits

DISPLAY:

Fluorescent display (Upper)
 Dot matrix display (Lower) (256 x 16 dots)

PRINTING SPEED:

3.2" (80mm) per second

PRESET KEYS:

92 one-touch preset keys
 Each key can be assigned two items using the shift key for a total of 184 presets

MEMORY CAPACITY:

Standard: 2MB

LABEL SIZE:

Label width: 1.5" - 2.5" (38mm - 64mm)
 Label length: 1.2" - 9.5" (30mm - 240mm)

COMMUNICATION:

TCP/IP 10/baseT
 DHCP support
 Ethernet

LABEL ROLL:

Inside diameter: 1.6" (40mm)
 Outside diameter: 3.9" (100mm)

WEIGHT:

24lbs.

POWER SUPPLY:

AC100 V / 120 V / 220 V / 240 V, 50/60 Hz

POWER CONSUMPTION:

Stand-by 50W
 In operation 100W

CLASSIFICATION:

NTEP certified, CC 95-057A6, UL listed

WARRANTY:

1-year limited warranty

DIMENSIONS

A: 15.75" (400mm)	H: 4.92" (125mm)
B: 9.84" (250mm)	I: 3.15" (80mm)
C: 2.56" (65mm)	J: 17.83" (453mm)
D: 8.86" (225mm)	K: 6.69" (170mm)
E: 16.53" (420mm)	L: 18.35" (466mm)
F: 6.69" (170mm)	M: 2.59" (65mm)
G: 12.44" (316mm)	N: 7.49" (190mm)

