

Ishida AC-4000D Scale with Printer



Available
January 2004!



Approvals



PART #	MODEL	CAPACITY
80316	AC-4000D	30lb x 0.01lb

Networking capabilities along with user-friendly operation make the new AC-4000D an ideal supermarket prep scale system for delis, seafood, meat and produce applications. The AC-4000D communicates via Ethernet, RF wireless communication, and supports Dynamic Host Configuration Protocol (DHCP). Choose from multiple label formats and utilize the powerful pre-pack feature for increased productivity.

The bright alphanumeric display provides valuable operation information including price, weight, and description.

Applications

- Meat, seafood, deli and produce departments
- Prepack operation

Standard Features

- Static or dynamic (DHCP) TCP/IP Ethernet communication
- Flash ROM for remote update of application software
- Increased productivity with large 230 mm (9 inches) label rolls
- Modular components work with any handwrap station
- System includes scale, keyboard/display, and printer
- Prints all legally required nutrition and safe handling information
- Flexible setup for ergonomic operation
- Stainless steel enclosure suitable for USDA applications
- 2 MB memory standard

Options/Accessories

- 46925[†]Scalemate unit wrap station - single printer (includes part #47673, #47674 & #47670)
- 47670.....Wrap station only - no wings, no scale hardware, overall dimensions: 22" W x 23" D x 32" H (558mm W x 584mm D x 812mm H)
- 53866.....Replacement heat pad cover for Scalemate, 15" W x 6" D (381mm W x 152mm D)
- 53962.....All-purpose shelf for Scalemate, 14" W x 34" D (355mm W x 863mm D)
- 46927.....Wrap station - right wing, 14" W x 22" D (355mm W x 558mm D)
- 47672.....Wrap station - left wing, 14" W x 22" D (355mm W x 558mm D)
- 53962.....Right wing with hood, 14" W x 34" D (355mm W x 863mm D)
- 47673.....Printer mounting hardware
- 47674.....Keyboard mounting hardware
- 46928.....Tabletop stand

LABEL STOCK

- 47738.....Pre-printed SH instructions
2.52" X 2.32" (64mm x 59mm)

COMMUNICATION HARDWARE

- 65231*ScaleLink Pro software
- 80309.....Internal 802.11b wireless communications (powered by Agere's™ Ruby™ RF chipset compatible with 802.11b/Wifi™ devices) PCMCIA card included

MANUALS

- 80815**Additional operator's manual
- 80816**Additional programmer's manual
- 80817**Service manual

SERVICE TOOLS

- 77369**CD-ROM contains (i-View, i-Label, firmware update tool, manuals)
- 77368.....BIOS Eprom kit

* License file required for operation. Must supply store name and address at time of order. One license required per location.

† Two film roll (without wings) base unit with printer and keyboard mounting brackets/hardware.

** Manuals and software programs can be downloaded for FREE from the distributor section of the Ishida web site at www.ishidaretail.com

CAPACITY/MINIMUM GRADUATION:

15 x 0.005lb/30 x 0.01lb (dual range)
 30 x 0.01lb (single range) selectable

DISPLAY ITEMS:

Tare: 4 digits
 Unit price: 5 digits
 Weight: 5 digits
 Total: 6 digits

DISPLAY:

Fluorescent display (Upper)
 Dot matrix display (Lower) (256 x 16 dots)

PRINTING SPEED:

3.2" (80mm) per second

PRESET KEYS:

92 one-touch preset keys.
 Each key can be assigned two items using the shift key for a total of 184 presets.

MEMORY CAPACITY:

Standard: 2MB

LABEL ROLL:

Maximum diameter: 9.0" (230mm)

WEIGHT:

47 lbs.

POWER SUPPLY:

AC100 V / 120 V / 220 V / 240 V, 50/60 Hz

POWER CONSUMPTION:

Standby: 50W
 Operation: 100W

CLASSIFICATION:

NTEP certified, CC 95-057A6, UL listed

WARRANTY:

1-year limited warranty

DIMENSIONS

A: 12.67" (322mm)	E: 15.74" (400mm)
B: 12.59" (320mm)	F: 10.00" (254mm)
C: 1.57" (40mm)	G: 15.74" (400mm)
D: 3.74" (95mm)	H: 7.87" (200mm)
	I: 14.56" (370mm)

